


Luminaire

Code 1217010A
Name nh1217 tavolo

Measur.

Code FTS1701940
Name nh1217 tavolo

Luminaire Flux	257.26 lm	Luminaire Power	4.00 W	Efficacy	64.31 lm/W	Efficiency	80.39%
Lamps Flux	320.00 lm	Maximum value	122.51 cd/klm	Position	C=0.00 G=179.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	140 mm 140 mm	Height Height	140 mm 140 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.015394 m2 0.019600 m2 0.019600 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.019600 m2 0.019600 m2 0.022742 m2	
Coordinate system Date Measurement Distance		CG 10-11-2017 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 320.00 lm	
Greenplux 4W E14 3000K 320 lm							
C.I.E. F UTE	14 36 64 30 80 --			D DIN 5040 B NBN		D12 BZ 10	



Luminaire

Code 1217010A
Name nh1217 tavolo

Measurem.

Code FTS1701940
Name nh1217 tavolo

Luminaire Flux	257.26 lm	Luminaire Power	4.00 W	Efficacy	64.31 lm/W	Efficiency	80.39%
Lamps Flux	320.00 lm	Maximum value	122.51 cd/klm	Position	C=0.00 G=179.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	140 mm 140 mm	Height Height	140 mm 140 mm		
Horizontal Luminous Area		0.015394 m2		Emitting area on Plane 180°		0.019600 m2	
Emitting area on Plane 0°		0.019600 m2		Emitting area on Plane 270°		0.019600 m2	
Emitting area on Plane 90°		0.019600 m2		Glare area at 76°		0.022742 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		10-11-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		320.00 lm	
Greenplux 4W E14 3000K 320 lm							
C.I.E.	14 36 64 30 80			D DIN 5040	D12		
F UTE	--			B NBN	BZ 10		

Apertura troppo larga

Apertura troppo larga