

Oplight

■ F4681009 - Textured White

Designed by Jasper Morrison

Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting	Wall	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	16
	LED Module	System Flux (lm)	1325

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Textured White	IP external	20
Length (mm)	193		
Net weight (kg)	0.9		
Gross weight (kg)	1.98		
IP	20		

Oplight

■ F4681030 - Satin Black

Designed by Jasper Morrison



Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting	Wall	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	16
	LED Module	System Flux (lm)	1325

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Satin Black	IP external	20
Length (mm)	193		
Net weight (kg)	0.9		
Gross weight (kg)	1.98		
IP	20		

Oplight

■ F4681032 - Textured metallic grey

Designed by Jasper Morrison



Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting	Wall	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	16
	LED Module	System Flux (lm)	1325

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Textured metallic grey	IP external	20
Length (mm)	193		
Net weight (kg)	0.9		
Gross weight (kg)	1.98		
IP	20		

Oplight

■ F4681033 - Textured anthracite

Designed by Jasper Morrison



Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting	Wall	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	16
	LED Module	System Flux (lm)	1325

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Textured anthracite	IP external	20
Length (mm)	193		
Net weight (kg)	0.9		
Gross weight (kg)	1.98		
IP	20		

Oplight

■ F4682009 - Textured White

Designed by Jasper Morrison



Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting Environment	Wall Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Number of heads	1
	LED Module	Source Power (W)	25
		System Flux (lm)	2065

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Textured White	IP external	20
Length (mm)	253		
Net weight (kg)	1.7		
Gross weight (kg)	3.75		
IP	20		

Oplight

■ F4682030 - Satin Black

Designed by Jasper Morrison



Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting	Wall	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	25
	LED Module	System Flux (lm)	2065

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Satin Black	IP external	20
Length (mm)	253		
Net weight (kg)	1.7		
Gross weight (kg)	3.75		
IP	20		

Oplight

■ F4682032 - Textured metallic grey

Designed by Jasper Morrison



Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting	Wall	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	25
	LED Module	System Flux (lm)	2065

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Textured metallic grey	IP external	20
Length (mm)	253		
Net weight (kg)	1.7		
Gross weight (kg)	3.75		
IP	20		

Oplight

■ F4682033 - Textured anthracite

Designed by Jasper Morrison



Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

Mounting	Wall	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	25
	LED Module	System Flux (lm)	2065

Optical

Lighting Type	Indirect
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main Voltage (Vac)	220-240
Dimmable	Yes
Dimming Interface	Remote Dimmable (Dimmer Not Included)

Physical

Colour	Textured anthracite	IP external	20
Length (mm)	253		
Net weight (kg)	1.7		
Gross weight (kg)	3.75		
IP	20		